

DESCRIPTION

The B3JC1654 is a 3-port, H-plane, X-band junction circulator designed for the low-cost marine radar market

SPECIFICATION

Electrical

Frequency range.....	9.1 to 9.3 GHz
Return loss (see note 1).....	20 dB min
Insertion loss.....	0.4 dB max
Isolation.....	20 dB min
Power handling (see note 2)...	30 kW peak
	30 W mean

Environmental

Operating temperature range...	- 30 to +75°C
Storage temperature range.....	- 40 to +90°C
Shock.....	100 g max

OUTLINE


Ref	Millimeters
A	50.0 ± 0.2
B	50.0 ± 0.5
C	50.0 ± 0.5
D	4.3 + 0.3 - 0.1
E	28.6 ± 0.2
F	32.5 ± 0.2
G	31.0 ± 0.2

MECHANICAL

Waveguide	WG16
Material	aluminium alloy
R.F. flanges	to mate with UG135/U MIL-F3922/54C PBR100
Weight	150 g approx

NOTES

1. Unused ports terminated in matched termination
2. Output port terminated with v.s.w.r 2.0:1 max.
3. The protective tape covering the waveguide must be removed before assembly
4. Strong magnetic fields may affect operation
Magnetic components must be kept at least 50 mm from the unit during operation



Whilst e2v technologies has taken care to ensure the accuracy of the information contained herein it accepts no responsibility for the consequences of any use thereof and also reserves the right to change the specification of goods without notice. e2v technologies accepts no liability beyond the set out in its standard conditions of sale in respect of infringement of third party patents arising from the use of tubes or other devices in accordance with information contained herein.

e2v technologies (uk) limited, Waterhouse Lane, Chelmsford, Essex CM1 2QU United Kingdom Holding Company: e2v technologies plc
Telephone: +44 (0)1245 493493 Facsimile: +44 (0)1245 492492
Contact e2v by e-mail: enquiries@e2v.com or visit www.e2v.com for global sales and operations centres.